

Exitflex low pressure hose grades and specifications

Application	Type Ref	Nom Bore Metric	Hose I/D "	Hose O/D mm	Max W.P. bars	Min B.P bars	Min Bend R mm	Temp Range °C	Inner Tube	Cover	Colour	Braid
LP Paint Hose	LP 1.12	20	3/4"	30	10	40		-40 +95	Polyamide	PU	BL	Polyester textile
	LP 1.8	13	1/2"	21.5	15	60		-40 +95	Polyamide	PU	BL	
LP Paint Hose Conductive	LPC 1.4	6	1/4"	11.8	20	80		-40 +95	Polyamide	PU	BK	
	LPC 1.5	8	5/16"	13.8	17	70		-40 +95	Polyamide	PU	BK	
	LPC 1.6	10	3/8"	15.5	15	60		-40 +95	Polyamide	PU	BK	
LP Paint Hose	LPV 1.4	6	1/4"	11.8	20	80		-40 +95	Polyamide	PU	BK	
	LPV 1.5	8	5/16"	13.8	15	60		-40 +95	Polyamide	PU	BK	
	LPV 1.6	10	3/8"	15.5	15	60		-40 +95	Polyamide	PU	BK	
	LPV 1.8	13	1/2"	19	12	50		-40 +95	Polyamide	PU	BK	
Foodstuff (FDA appr.) Chemical Multipurpose Beverages	LF 1.4	6	1/4"	12.3	20	80	90	-40 +95	FEP - 140 Teflon	PU	TR	
	LF 1.6	10	3/8"	15.3	15	60	130	-40 +95	FEP - 140 Teflon	PU	TR	
	LF 1.8	13	1/2"	21	12	50	180	-40 +95	FEP - 140 Teflon	PU	TR	
LP Paint Hose	LM 1.4	6	1/4"	10.3	20	80		-40 +95	Polyamide	PU	TR	Polyester textile
	LM 1.5	8	5/16"	12	17	70		-40 +95	Polyamide	PU	TR	
	LM 1.6	10	3/8"	14	15	60		-40 +95	Polyamide	PU	TR	
LP Paint Hose Conductive	LMC 1.4	6	1/4"	10.3	20	80		-40 +95	Polyamide	PU	TR	
	LMC 1.5	8	5/16"	12	17	70		-40 +95	Polyamide	PU	TR	
	LMC 1.6	10	3/8"	14	15	60		-40 +95	Polyamide	PU	TR	
LP Paint Hose	MA 1.3	4	3/16"	8.5	7	30		-40 +95	Polyamide	PU	TR	Not Applicable
	MA 1.4	6	1/4"	10.3	7	30		-40 +95	Polyamide	PU	BK	
	MA 1.5	8	5/16"	12	6	24		-40 +95	Polyamide	PU	BK	
	MA 1.6	10	3/8"	14	5	20		-40 +95	Polyamide	PU	TR	
Air hose	MO 1.4	6	1/4"	10.3	7	30		-40 +95	Polyester	PU	BN	
	MO 1.5	8	5/16"	12	6	24		-40 +95	Polyester	PU	BN	
	MO 1.6	10	3/8"	14	5	20		-40 +95	Polyester	PU	BN	
Antistatic hose	MON 1.4	6	1/4"	10.3	7	30		-40 +95	Polyester	PU	BN	

Colour codes: BN (Blue Navy), RD (Red), BK (Black), BL (Blue light), BZ (Bronze); TR (Translucent).