

Fluid Control

TYPE REF	DESCRIPTION
----------	-------------

Needle Valves

- | | |
|-----------|---|
| 78-200/34 | 1/4" needle shut off valve 2 x 1/4 BSP F inlets
Stainless steel 6000 PSI MWP |
| 78-201/34 | 3/8" needle shut off valve 2 x 3/8 BSP F inlets
Stainless steel 6000 PSI MWP |
| 78-202/34 | 1/2" needle shut off valve 2 x 1/2 BSP F inlets
Stainless steel 6000 PSI MWP |



Ball Valves

- | | |
|-----------|---|
| 78-205/4 | High pressure ball valve 400 Bar MWP
1/4 BSP F x 1/4 BSP F |
| 78-205/34 | High pressure ball valve 400 Bar MWP
1/4 BSP F x 1/4 BSP F stainless steel |
| 78-206/4 | High pressure ball valve 400 Bar MWP
3/8 BSP F x 3/8 BSP F |
| 78-218/4 | High pressure 3 way L ported ball valve 400 Bar MWP
3 x 3/8 BSP(F) |
| 78-208/15 | LP ball valve 1/4" F swivel nut 1/4 BSP (M). Brass nickel plated |
| 78-209/15 | LP ball valve 1/4 FBE. Brass nickel plated |
| 78-215/15 | LP ball valve 3/8 MBE. Brass nickel plated |
| 78-216/15 | LP ball valve 3/8 FBE. Brass nickel plated |



78-205/34



- | | |
|-----------|---|
| 78-323/30 | LP ball valve 1/4 BSP (M). Flat face x 1/4 BSP (M). Cone face,
PTFE seals, stainless steel |
|-----------|---|



- | | |
|-----------|---|
| 78-324/30 | LP ball valve 3/8 BSP (M). Flat face x 3/8 BSP (M). Cone face,
PTFE seals, stainless steel |
|-----------|---|



Quick Detach Fluid Couplings

Quick Detach Low Pressure Hi-Flo Fluid Couplings
Fully stainless steel, easy to operate, high flow rate, stems & couplings available separately
seal kits available

- | | |
|-----------|---|
| 78-311/34 | Fluid QD connection - new design featuring hexagon body |
| 78-312/34 | New design stem for above featuring loose nut |

78-312/34 78-311/34

