

# Mixing Tanks

## PM60 -250

The 60-250 package makes the preparation and use of spray applied materials simple and clean to handle whilst at the same time helps to ensure that your material achieves and remains at the correct specification - ready for use

It comprises a standard industrial 25 litre pail with stainless steel lid, which fastens to the pail using three external fixings.

The lid itself is spun and laser profiled has a filler/viewer point with pear shaped access plate, a 1/2BSP male connection fluid suction tube (reaching the bottom of the pail) and a PM-60 pneumatic mixer.



### Standard Features

- Light weight
- High quality function
- Stainless steel shaft & propeller
- Long service life
- Integral speed control & silencer

### Technical Data

- Air pressure for operation 0.5 to 8Bar
- Speed @ 4 Bar = 900RPM
- Air consumption = 100L/min
- Output = 60 Watts
- Weight (excluding stand) = 1.10kg
- Standard shaft length = 440mm
- Propeller diameter = 70mm

PM60-250

Pail mounted Agitator Assy



100 litre model



45 litre model

Exitflex now design manufacture and supply stainless steel mixing tanks to meet your exact specifications. Supplied with pneumatic operation mixers, fillers/viewers, bottom outlet ball valve connections.

Please allow us the opportunity to quote against your mixing vessel requirements.