

Low Pressure Tubing and Connections

Nylon Tubing

30 metre coils. Stock colour natural. Black, blue, red, green available to special order. Larger coils to special order. Metric sizes. Imperial sizes also available, please enquire. NB: Hoses listed on this page are all non-conductive



TYPE REF	OD mm	ID mm	MWP PSI	30m COIL	TYPE REF	OD mm	ID mm	MWP PSI	30m COIL
ENF 4/25	4	2.5	377		ENF 5/3	5	3	348	
ENF 5/33	5	3.3	225		ENF 6/4	6	4	225	
ENF 6/45	6	4.5	275		ENF 8/55	8	5.5	310	
ENF 8/6	8	6	250		ENF 10/7	10	7	310	
ENF 10/8	10	8	250		ENF 12/8.5	12	8.5	304	
ENF 12/10	12	10	200		ENF 15/12	15	12	200	
ENF 16/12	16	12	260		ENF 18/14	18	14	225	
ENF 22/17	22	17	225		ENF 28/22	28	22	220	

PTFE Tubing

TYPE REF	OD m	ID mm		25m COIL	TYPE REF	OD mm	ID mm		25m COIL
PTFE 4/25	4	2.5	-		PTFE 10/8	10	8	-	
PTFE 6/4	6	4	-		PTFE 12/10	12	10	-	
PTFE 8/5	8	5	-						
PTFE 8/6	8	6	-						

NB. Other sizes by enquiry.

Polyethylene Tubing

30 metre coils. Stock colour natural

TYPE REF	OD mm	ID mm	MWP PSI	30m COIL	TYPE REF	OD mm	ID mm	MWP PSI	30m COIL
EPF 6/4	6	4	180		EPF 8/6	8	6	150	
EPF 10/8	10	8	120						

76 Series Tubing Connections

Stainless steel wetted section-ideal for water based materials

TYPE REF	DESCRIPTION
76-032/39	1/4 BSP(F) for 4x6mm tubing
76-069/39	3/8 BSP(F) for 4x6mm tubing
76-031/39	1/4 NPSM(F) for 4x6mm tubing
76-068/39	3/8 NPSM(F) for 4x6mm tubing
76-142/39	1/4 BSP(F) for 6x8mm tubing
76-179/39	3/8 BSP(F) for 6x8mm tubing
76-141/39	1/4 NPSM(F) for 6x8mm tubing
76-178/39	3/8 NPSM(F) for 6x8mm tubing
76-252/39	1/4 BSP(F) for 8x10mm tubing
76-289/39	3/8 BSP(F) for 8x10mm tubing
76-251/39	1/4 NPSM(F) for 8x10mm tubing
76-288/39	3/8 NPSM(F) for 8x10mm tubing
76-289/39	3/8 BSP(F) for 8x10mm tubing



These connections feature a 'loose' nut and 60 degree cone seat.

Connectors are available in 3/8 and 1/4 BSP and NPSM forms.

The wetted section is stainless steel 304 and the ferrule and nut are nickel plated brass, supplied with a spring guard as standard.